

TECHNICAL DATASHEET

Endura Kolormax



www.ja-int.com | +44 (0)1790 752 757 J&A (International) Ltd. Insignia House, Vale Road, Spilsby, Lincolnshire PE23 5HE

Endura Kolormax



TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C):190°CTemperature (°F):374°FTime:12 secondsPressure:High56.9 - 71.1 psi / 3.9 - 4.9 bar / 4.0 - 5.0 kg/cm2Carrier Release:Instant/Hot peel

LAUNDERING

Suitable for Industrial Laundering up to 85°C Suitable for Industrial Drying Techniques - Medium Suitable for Dry-Cleaning Iron - Medium, On Reverse Do Not Bleach Do Not wash with strong Acid or Alkaline additives

HANDLING AND STORAGE

Store in a damp-free environment at a stable temperature of ~20°C Keep away from direct sunlight No personal protection equipment is required in handling and storage Do not attempt to apply any transfer that has been removed from its carrier

COMPOSITION

Ink - Digital & Water Based Adhesive - Polyester Carrier - Coated Polyester Sheeting

HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user No PPE is required during application**

ENVIRONMENTAL / RECYCLING

All inks are compostable Polyester carrier - non-recylable Vegan-Friendly: No

CERTIFICATION Wash Stability: EN ISO 15797